



APPLICABLE BUILDING CODES

1. IBC

2. UFC 1–200–01

3. UFC 3–600–01

4. UFC 3–600–10N

5. NFPA 10

6. NFPA 13

7. NFPA 70

8. NFPA 72

9. NFPA 90A

10. NFPA 101

11. UFAS

12. ABA
- INTERNATIONAL BUILDING CODE, 2012 (IBC)

GENERAL BUILDING REQUIREMENTS, 1 SEPTEMBER 2013

FIRE PROTECTION ENGINEERING FOR FACILITIES, 1 MARCH 2013

FIRE PROTECTION ENGINEERING, FINAL DRAFT, AUGUST 2007

STANDARD FOR PORTABLE FIRE EXTINGUISHERS, 2013

STANDARD FOR THE INSTALLATION OF SPRINKLER SYSTEMS, 2013

NATIONAL ELECTRIC CODE, 2014

NATIONAL FIRE ALARM & SIGNALING CODE, 2013

INSTALLATION OF AIR–CONDITIONING AND VENTILATING SYSTEMS, 2012

LIFE SAFETY CODE, 2012 (LSC)

UNIFORM FEDERAL ACCESSIBILITY STANDARDS

ARCHITECTURAL BARRIERS ACT

USE ROOM OCCUPANCY

- B

S–1

A–2
- BUSINESS (IBC 304.1, LSC 6.1.11) – ORDINARY HAZARD (LSC 38.1.5)

INDUSTRIAL (IBC 311.2, LSC 6.1.12) – ORDINARY HAZARD (LSC 40.1.2.1.1)

ACCESSORY ASSEMBLY (IBC 303.3, LSC 6.1.2.1) – ORDINARY HAZARD (LSC 12.1.5)

FIRE PROTECTION SYSTEMS

WET PIPE SPRINKLER SYSTEM  
FIRE ALARM SYSTEM

CONSTRUCTION TYPE

BUILDING 4224 TYPE II–B

ALLOWABLE AREA HEIGHT

UNLIMITED AREA TWO–STORY GROUPS B & S–1 BUILDING (IBC 507.4)

BASIC ALLOWABLE STORIES/HEIGHT (IBC TABLE 503):

INCREASE FOR AUTOMATIC SPRINKLERS (IBC 504.2):

TOTAL ALLOWABLE STORIES/HEIGHT:

2/55 FT.

1/20 FT.

3/75 FT.

ACTUAL AREA HEIGHT

TOTAL FOOTPRINT FLOOR AREA

TOTAL BUILDING HEIGHT

137,260 SQ. FT.

2 STORY/49 FT.

FIRE RESISTANCE RATING REQUIREMENTS FOR BUILDING ELEMENTS

(IBC TABLE 601, TYPE II–B CONSTRUCTION)

STRUCTURAL FRAME, INCL. COLUMNS, GIRDERS & TRUSSES

BEARING WALLS, INTERIOR & EXTERIOR

NON–BEARING WALLS, INTERIOR & EXTERIOR

FLOOR CONSTRUCTION

ROOF CONSTRUCTION

0 HR

0 HR

0 HR

0 HR

0 HR

INTERIOR WALLS

EXTERIOR FIRE–RESISTANCE RATING BASED ON FIRE SEPARATION DISTANCE (TYPE II–B)

FIRE SEPARATION DISTANCE (FSD)	GROUP B	GROUP S–1
FSD < 5 FT.	1 HR.	2 HR.
5 FT. < FSD < 10 FT.	1 HR.	1 HR.
FSD > 10 FT.	0 HR.	0 HR.

THE BUILDING IS LOCATED MORE THAN 40–FEET FROM ANY SURROUNDING STRUCTURES; THEREFORE, NO EXTERIOR WALL RATINGS ARE REQUIRED BASED ON FIRE SEPARATION DISTANCE ARE REQUIRED.

INTERIOR FIRE RESISTANCE REQUIREMENTS

INCIDENTAL USE AREAS/SPECIAL HAZARD/TELECOMMUNICATIONS.

ROOM	REQUIRED SEPARATION
BOILER/FURNACE ROOMS	SPRINKLER W/SMOKE PARTITIONS (LSC 38.3.2.1)
GENERAL STORAGE ROOMS	SPRINKLER W/SMOKE PARTITIONS (LSC 38.3.2.1)

INTERIOR FINISH CLASSIFICATION

LIMITS (BASED ON ASSEMBLY OCCUPANCY WITH PERMITTED REDUCTION FOR SPRINKLERS):  
EXITS (TABLE A.10.2.2)  
EXIT ACCESS CORRIDORS (TABLE A.10.2.2)  
OTHER SPACES (TABLE A.10.2.2)  
FLOOR FINISH IN EXITS & EXIT ACCESS CORRIDORS

MINIMUM CLASS B  
MINIMUM CLASS C  
MINIMUM CLASS C  
NO REQUIREMENT

MEANS OF EGRESS

MULTIPLE, MIXED OCCUPANCY PER LSC 6.1.14.1.1. MEANS OF EGRESS AND OTHER SAFEGUARDS SHALL COMPLY WITH THE MOST RESTRICTIVE REQUIREMENTS.

OCCUPANT LOADS (LSC TABLE 7.3.1.2)

BUSINESS

GENERAL INDUSTRIAL

ASSEMBLY (LESS CONCENTRATED)

KITCHEN

MEP/STORAGE

100 SQ. FT./PERSON

100 SQ. FT./PERSON

15 SQ. FT./PERSON

100 SQ. FT./PERSON

500 SQ. FT./PERSON

AREA	SPACE USE	APPROX. AREA (SQ. FT.)	OCCUPANT LOAD FACTOR (SQ. FT./PERSON)	OCCUPANT LOAD (PERSONS)
FIRST FLOOR				
OFFICE AREA	BUSINESS	3,073	100	31
LOUNGE	ASSEMBLY	600	15	40
SHOP AREA	GENERAL INDUSTRIAL	118,816	100	1,188
STORAGE	STORAGE	8,033	500	16
UTILITY ROOMS	MEP SPACE	6,738	500	22
TOTAL		137,260	–	1,297
SECOND FLOOR				
OFFICE AREA	BUSINESS	11,496	100	115
CONFERENCE ROOM	ASSEMBLY	689	15	46
SHOP AREA	GENERAL INDUSTRIAL	18,548	100	185
KITCHEN	KITCHEN	400	100	4
CAFETERIA	ASSEMBLY	1,850	15	123
STORAGE	STORAGE	337	500	1
TOTAL		31,955	–	474

TRAVEL DISTANCES

COMMON PATH OF TRAVEL (LSC TABLE A.7.6): (ASSEMBLY/BUSINESS/INDUSTRIAL):

TOTAL TRAVEL DISTANCE (LSC TABLE A.7.6): (ASSEMBLY/BUSINESS/INDUSTRIAL):

DEAD END CORRIDOR (LSC TABLE A.7.6): (ASSEMBLY/BUSINESS/INDUSTRIAL):

\*20 FT FOR > 50 PERSONS & 75 FT FOR < 50 PERSONS

20–75\*/100/100 FT.

250/300/250 FT.

20/50/50 FT.

THE MAXIMUM TRAVEL DISTANCE ON THE FIRST FLOOR IS 245–FT FROM THE MAIN SHOP AREA.

THE MAXIMUM COMMON PATH OF TRAVEL ON THE FIRST FLOOR IS 80–FT FROM THE NEW DISASSEMBLY SHOP.

CAPACITY OF EXITS

CAPACITY OF EXITS (LSC TABLE 7.3.3.1):

LEVEL COMPONENTS (WIDTH/PERSON)

STAIRS (WIDTH/PERSON)

0.2 IN/PERSON

0.3 IN/PERSON

NUMBER OF EXITS (LSC 7.4)

1 FOR ORDINARY HAZARD INDUSTRIAL OCCUPANCIES WHEN THE TRAVEL DISTANCE IS LESS THAN OR EQUAL TO THE COMMON PATH OF TRAVEL (LSC 40.2.4.1.2).

2 FOR OCCUPANT LOAD < 500

3 FOR OCCUPANT LOAD > 500 AND < 1,000

4 FOR OCCUPANT LOAD > 1,000

FLOOR LEVEL	REQUIRED EXIT CAPACITY	AVAILABLE EXIT CAPACITY	NUMBER OF EXITS REQUIRED	NUMBER OF EXITS PROVIDED
FIRST FLOOR	1,297	5,160 3 – 4’–0” WIDE STAIRS 22 – 3’–0” WIDE DOORS 2 – 6’–0” WIDE DOORS	4	27
SECOND FLOOR	474	588 4 – 3’–8” WIDE STAIRS	2	4

ADDITIONAL LIFE SAFETY CRITERIA

MEANS OF EGRESS SHALL BE ILLUMINATED. ARTIFICIAL LIGHTING SHALL BE PROVIDED.

EMERGENCY LIGHTING SYSTEMS SHALL BE PROVIDED WITH BATTERY PACK AT FIXTURE IN EVENT OF LOSS OF POWER.

EXIT SIGNS SHALL BE PROVIDED AT ALL EXIT DOORS AND WITHIN THE EXIT ACCESS TO DIRECT OCCUPANTS TO AN EXIT.

PORTABLE FIRE EXTINGUISHERS SHALL BE LOCATED AND INSTALLED PER NFPA 10 WITH 75 FOOT MAXIMUM TRAVEL DISTANCE TO AN EXTINGUISHER.

LEGEND

- XXX

XXX

XXX

ROOM AREA (SQ. FT.)
- XXX

XXX

XXX
- OCCUPANT LOAD (SQ. FT./PERSON)

XXX

XXX

XXX

NUMBER OF OCCUPANTS (PERSONS)

##

##

##

REQUIRED EGRESS CAPACITY

##

##

##

PROVIDED EGRESS CAPACITY

TD = XX FT

CP = XX FT

TRAVEL DISTANCE

COMMON PATH OF TRAVEL

3–HR FIRE–RESISTANCE RATING

FE

NEW WALL–MOUNTED FIRE EXTINGUISHER

FE

EXISTING TO REMAIN WALL–MOUNTED FIRE EXTINGUISHER

APPROVED

ACTIVITY – SATISFACTORY TO

DATE

APPROVED

FOR EFD FOR COMMANDER NAVFAC

DATE

A/E

EFD

APF DESIGN

DEG DRAWN

AJW REVIEW

AJW QC

AJW CHIEF ARCH./ ENGR

PROJECT MANAGER

FIRE PROTECTION

BRANCH MANAGER

DESIGN DIRECTOR

DEPARTMENT OF THE NAVY

NAVAL FACILITIES ENGINEERING COMMAND

MARINE CORPS AIR STATION, CHERRY POINT, N.C.

CONSTRUCT COMPOSITE SHOP ADDITION, BUILDING 4224

BUILDING CODE AND LIFE SAFETY ANALYSIS

STA. PROJ. NO. 6328570

SPEC. NO.


CONSTR. CONTR. NO.

NAVFAC DRAWING NO. 12685638

SHEET 25 OF 45

LS00

100% Final Submittal







1. GENERAL SCOPE — MODIFY THE EXISTING ADDRESSABLE FIRE ALARM SYSTEM IN BUILDING 4224 TO COORDINATE WITH THE ADDITION OF THE DISASSEMBLY SHOP. THE EXISTING FIRE ALARM CONTROL PANEL BY JCI IS LOCATED IN THE MAIN LOBBY.
2. APPLICABLE CODES:

UFC 1-200-01	GENERAL BUILDING REQUIREMENTS, 1 SEPTEMBER 2013.
UFC 3-600-01	FIRE PROTECTION ENGINEERING FOR FACILITIES, 1 MARCH 2013.
UFC 3-600-10N	FIRE PROTECTION ENGINEERING, AUGUST 2007
NFPA 70	NATIONAL ELECTRIC CODE (NEC), 2014.
NFPA 72	NATIONAL FIRE ALARM CODE, 2013.

3. NEW DEVICES SHALL BE UL LISTED.
4. SIGNALING LINE AND INITIATING DEVICE CIRCUITS SHALL MATCH EXISTING CLASS DESIGNATION.
5. ALL NEW CONDUIT AND BACK BOXES SHALL BE CONCEALED UNLESS OTHERWISE NOTED. ALL NEW JUNCTION BOXES AND COVERS SHALL BE PAINTED RED IN UNFINISHED AREAS. IN FINISHED AREAS, CONDUIT AND JUNCTION BOXES SHALL BE PAINTED TO MATCH THE ROOM FINISH. ALL NEW JUNCTION BOXES SHALL HAVE A PERMANENT, MACHINE PRINTED LABEL READING "FIRE ALARM CIRCUIT" ON THE INSIDE COVER. ALL FIRE ALARM CONDUITS IN FINISHED AREAS SHALL BE MARKED WITH  $\frac{3}{4}$ -IN RED BANDS EVERY 10 FEET, AT EACH SIDE OF A FLOOR, WALL, OR CEILING PENETRATION.
6. ALL WIRING, CABLES, BOXES, TROUGHS AND OTHER RELATED EQUIPMENT SHALL BE INSTALLED IN STRICT COMPLIANCE WITH THE NATIONAL ELECTRICAL CODE (NEC).
7. ALL PENETRATIONS OF FIRE RESISTANCE RATED BARRIERS, WALLS, AND, SHAFT/ASSEMBLIES SHALL BE DRILLED AND THEN SEALED WITH AN APPROVED UL FIRE-RATED THROUGH-PENETRATION ASSEMBLY.
8. UL CLASSIFICATIONS AND MATERIAL PRODUCT DATA SHEETS FOR ALL FIRE STOPPING SYSTEMS SHALL BE SUBMITTED AND APPROVED BEFORE ANY FIRE STOPPING IS INSTALLED.
9. 25% SPARE CAPACITY SHALL BE PROVIDED ON NEW INDIVIDUAL CIRCUITS.
10. SECONDARY POWER SUPPLY SHALL BE VIA LEAD CALCIUM BATTERY CAPABLE OF OPERATING THE FIRE ALARM SYSTEM ON STANDBY FOR 48 HOURS FOLLOWED BY 10 MINUTES IN ALARM. CHARGING AND METERING SHALL BE PROVIDED IN ACCORDANCE WITH NFPA 72.
11. ALL DRAWINGS ARE CONCEPTUAL IN NATURE. THEY DO NOT SHOW THE EXACT LOCATIONS OF COMPONENTS NOR SHOW ALL SYSTEM COMPONENTS. CONTRACTOR SHALL PROVIDE ADDITIONAL COMPONENTS FOR A PROPERLY INSTALLED AND FUNCTIONAL SYSTEM IN ACCORDANCE WITH ALL APPLICABLE CODES.
12. DEDICATED BATTERY CABINETS SHALL BE MOUNTED NO MORE THAN 3 FEET FROM THE FINISHED FLOOR.




NOTE: NOT ALL DEVICES ARE INDICATED IN THE DIAGRAM  
SYMBOLS MAY REPRESENT MULTIPLE DEVICES, APPLIANCES  
AND CIRCUITS.

1 FIRE ALARM RISER DIAGRAM  
FA001FA001 SCALE: NOT TO SCALE

FIRE ALARM INPUT	OPERATION											
	ACTIVATE AUDIBLE AND VISUAL FA EVACUATION	ALARM CONDITION AT FACP	SUPERVISORY CONDITION AT FACP	TROUBLE CONDITION AT FACP	TRANSMIT ALARM SIGNAL TO FACP	SHUT DOWN AIR HANDLING UNIT	ACTIVATION OF ELEVATOR RECALL TO FIRE DEPT. VIA DIAC1	ILLUMINATE FIREFIGHTER'S SERVICE SIGNAL (CONSTANT)	ILLUMINATE FIREFIGHTER'S SERVICE SIGNAL (FLASH)	SHUNT TRIP POWER TO ELEVATOR (NO TIME DELAY)		
MANUAL PULL STATION	●	●			●							
AUTOMATIC SPRINKLER FLOW SWITCH	●	●			●							
AUTOMATIC SPRINKLER SYSTEM TAMPER SWITCH			●									
AREA SMOKE DETECTOR ACTIVATION	●	●			●							
DUCT SMOKE DETECTOR ACTIVATION			●			●						
FIRST FLOOR ELEVATOR LOBBY SMOKE DETECTOR ACTIVATION	●	●			●		●	●				
SECOND FLOOR ELEVATOR LOBBY SMOKE DETECTOR ACTIVATION	●	●			●	●		●				
ELEVATOR MACHINE ROOM SMOKE DETECTOR ACTIVATION	●	●			●	●			●			
ELEVATOR MACHINE ROOM WATER FLOW SWITCH	●	●			●						●	
ELEVATOR SHUNT TRIP POWER FAILURE			●									
FACU CIRCUIT FAULT (OPEN, GROUND, SHORT)				●								
OTHER TROUBLE CONDITION				●								

# FIRE ALARM SEQUENCE OF OPERATIONS

[illegible]





◻ FIRE PROTECTION ◻ GENERAL NOTES◻

1. GENERAL SCOPE: EXTEND THE EXISTING SPRINKLER SYSTEM TO PROTECT THE DISASSEMBLY SHOP ADDITION.
2. APPLICABLE CODES:

UFC 1-200-01	GENERAL BUILDING REQUIREMENTS, 1 SEPTEMBER 2013.
UFC 3-600-01	FIRE PROTECTION ENGINEERING FOR FACILITIES, 1 MARCH 2013.
UFC 3-600-10N	FIRE PROTECTION ENGINEERING, AUGUST 2007
NFPA 13	INSTALLATION OF SPRINKLER SYSTEMS, 2013.
3. THE CONTRACTOR SHALL HAVE A DESIGNER WITH A NICET LEVEL III CERTIFICATION IN WATER-BASED FIRE PROTECTION SYSTEM LAYOUT OR A LICENSED PROFESSIONAL FIRE PROTECTION ENGINEER IN RESPONSIBLE CHARGE OF THE SYSTEM DESIGN.
4. WET PIPE SPRINKLER PIPE SHALL BE UL LISTED BLACK STEEL, MINIMUM SCHEDULE 40 FOR ALL PIPE DIAMETERS LESS THAN 2-INCH. WET PIPE SPRINKLER PIPE SHALL BE UL LISTED BLACK STEEL, MINIMUM SCHEDULE 10 FOR ALL PIPE DIAMETERS 2-INCH AND LARGER
5. THE DISASSEMBLY SHOP SHALL BE CLASSIFIED AS HAZARD CATEGORY 2.
6. SPRINKLERS SHALL HAVE A MINIMUM K FACTOR OF 8.0 IN HAZARD CATEGORY 2 AREAS.
7. UPRIGHT SPRINKLERS SHALL BE INSTALLED IN THE DISASSEMBLY SHOP.
8. PROVIDE QUICK-RESPONSE SPRINKLERS IN ALL SPACES.
9. PROVIDE A MINIMUM OF TWO SPARE SPRINKLERS OF EACH TYPE AND TEMPERATURE CLASSIFICATION.
10. SPRINKLER SYSTEM SHALL BE HYDRAULICALLY DESIGNED.
11. ALL PIPE PENETRATIONS THROUGH FIRE RATED BARRIERS SHALL BE PROVIDED WITH U.L. LISTED FIRE STOP SYSTEMS. THIS INCLUDES BUT IS NOT LIMITED TO STAIRS, FLOORS, CEILINGS AND SHAFTS.
12. UL CLASSIFICATIONS AND MATERIAL PRODUCT DATA SHEETS FOR ALL FIRE STOPPING SYSTEMS SHALL BE SUBMITTED AND APPROVED BEFORE ANY FIRE STOPPING IS INSTALLED.
13. AVAILABLE WATER SUPPLY TEST DATA IS AS FOLLOWS:

DATE TEST PERFORMED:	11/5/2014
STATIC PRESSURE (WFH-1009):	46 PSI
RESIDUAL PRESSURE (WFH-1002):	44 PSI
FLOW RATE:	1,015 GPM
14. THESE DRAWINGS DEMONSTRATE THE CONFIGURATION OF MAJOR SYSTEM COMPONENTS. THEY ARE DIAGRAMMATIC IN NATURE AND ARE NOT INTENDED TO SHOW EXACT LOCATIONS. PIPE LENGTHS AND ELEVATIONS INDICATED ON THE DRAWINGS (IF SHOWN) ARE APPROXIMATE. COORDINATE FINAL INSTALLATION WITH ACTUAL FIELD CONDITIONS AND OTHER CONSTRUCTION TRADES. THE CONTRACTOR SHALL DESIGN THE SPRINKLER SYSTEM TO PROVIDE COMPLETE PROTECTION THROUGHOUT IN ACCORDANCE WITH NFPA13.

□IRE PROTECTION LE□ END□

----- EXISTING TO REMAIN SPRINKLER PIPING  
 \_\_\_\_\_ SPRINKLER PIPING  
 - - - - - EXTENT OF SPRINKLER WORK


## OCCUPANCY HAZARD INFORMATION

THE DISASSEMBLY SHOP SHALL BE HAZARD CATEGORY 2. A MINIMUM DENSITY OF 0.20 GPM/SQ.FT. WITH A DESIGN AREA OF 2,500 SQ.FT. AND A HOSE ALLOWANCE OF 250 GPM SHALL BE USED. SPRINKLER LAYOUT SHALL BE IN ACCORDANCE WITH NFPA 13 ORDINARY HAZARD SPACING.



DESIGNED &amp; ENGINEERED BY

MBF ARCHITECTS PA   
17-C Pollock Street, New Bern, NC 28560 Tel. 252.637.6131



APPROVED

ACTIVITY - SATISFACTORY TO

ATE

APPROVED

OR EFD FOR COMMANDER NAVFAC

ATE

A/F	EFD
-----	-----

APF	DESIGN	_____
DEG	DRAWN	_____
AJW	REVIEW	_____
AJW	QC	_____
AJW	CHIEF ARCH./ ENGR.	_____

PROJECT MANAGER \_\_\_\_\_  
FIRE PROTECTION \_\_\_\_\_  
BRANCH MANAGER \_\_\_\_\_  
DESIGN DIRECTOR \_\_\_\_\_

MARINE CORPS AIR STATION, CHERRY POINT, N.C.  
 CONSTRUCT COMPOSITE SHOP  
 ADDITION, BUILDING 4224  
 FIRE PROTECTION GENERAL NOTES AND ILLUSTRATIONS

TA PROJ. NO. 6328570

PEC. NO.


CONSTR. CONTR. NO.


AVFAC DRAWING NO.




SHEET 29 OF 45

□ □ 00 □



**100% Final Submitt**





APPROVED	DATE	DESCRIPTION	SYMBOL	DATE	APPROVED
 DESIGNED & ENGINEERED BY:   APPROVED ACTIVITY - SATISFACTORY TO DATE FOR EFD FOR COMMANDER NAVFAC DATE A/E PRC DESIGN PRC DRAWN PRC REVIEW JTR QC JRC CHIEF ARCH/ ENGR PROJECT MANAGER FIRE PROTECTION BRANCH MANAGER DESIGN DIRECTOR					
NAVAL FACILITIES ENGINEERING COMMAND MARINE CORPS AIR STATION, CHERRY POINT, N.C. CONSTRUCT COMPOSITE SHOP ADDITION, BUILDING 4224 PARTIAL FLOOR PLAN [PLUMBING] DEMOLITION					
STA. PROJ. NO. 6328570 SPEC. NO. CONSTR. CONTR. NO. NAVFAC DRAWING NO. 12685644 SHEET 31 OF 45 <b>P-100</b> 100% Final Submittal					




[illegible]













PACKAGED ROOFTOP UNIT SCHEDULE																								
MARK	LOCATION	MANUFACTURER MODEL	SUPPLY AIR (CFM)	OUTSIDE AIR (CFM)	SUPPLY FAN				DX COOLING						ELECTRIC HEAT			PREFILTER	ELECTRICAL			WEIGHT (LBS)	NOTES	
					CFM	E.S.P. "W.C.	BHP	HP	TOTAL MBH	SENS. MBH	EAT (°F)		LAT (°F)		EER	KW	EAT (°F)		LAT (°F)	MCA	MOCP			VOLT/PH/Hz
											DB	WB	DB	WB										
AHU-1	ROOF	TRANE WSC120	4,000	400	4,000	1.0	1.7	3.0	143.2	92.9	80.0	67.0	58.8	55.4	9.8	36	70.0	104.0	2"	87.0	90	480/3/60	2000	1,2,3,4,5

NOTES:

1. PROVIDE WITH MERV 8 PREFILTER.
2. PROVIDE WITH SINGLE POINT ELECTRICAL CONNECTION.
3. PROVIDE WITH ROOF CURB SUITABLE FOR SLOPED ROOF.
4. PROVIDE WITH 120V/1 CONVENIENCE OUTLET, POWERED VIA UNIT SINGLE POINT CONNECTION PER NOTE 2 ABOVE.
5. PROVIDE SUPPLEMENTAL ELECTRIC HEAT WITH SCR CONTROL.

AIR DISTRIBUTION SCHEDULE						
MARK	DESCRIPTION	NECK SIZE	PANEL SIZE	TYPE	DISCHARGE PATTERN	NOTES
A	STEEL REGISTER, LOUVERED FACE, 0° DEFLECTION	20x20	20x20	SUPPLY	1-WAY	1
R1	ALUMINUM, EGG CRATE	76x20	76x20	RETURN	N/A	1

NOTES:

1. PROVIDE WITH WHITE, BAKED ENAMEL FINISH.

OUTSIDE AIR CALCULATION (2009 IMC)										
UNIT MARK	FLOOR AREA (SQ.FT.)	ASHRAE CLASSIFICATION	PEOPLE PER 1000 SF	TOTAL PEOPLE	CFM PER PERSON	CFM PER SQ. FT.	REQUIRED CFM	TOTAL REQUIRED CFM	TOTAL PROVIDED CFM	NOTES
AHU-1	1,452	GENERAL MANUFACTURING	10	15	5	0.18	334	334	400	1
TOTAL								334	400	

NOTES:

1. PER ASHRAE 62.1-2010.

[illegible]



**100% Final Submittal**



1

2

3

4

5

6

GENERAL NOTES AND REQUIREMENTS.

1. WORKMANSHIP SHALL CONFORM TO NECA PUBLICATION "STANDARDS OF INSTALLATION."

2. INSTALLATION SHALL COMPLY WITH NATIONAL ELECTRICAL CODE, STATE BUILDING CODE, AND ALL REQUIREMENTS OF THE LOCAL INSPECTOR (FURNISH INSPECTION CERTIFICATE). ALL WORK SHALL BE BY LICENSED ELECTRICAL CONTRACTOR.

3. THE CONTRACTOR SHALL REFER TO THE ARCHITECTURAL PLANS FOR FLOOR PLAN DIMENSIONS. DO NOT SCALE THESE DRAWINGS.

4. THE CONTRACTOR SHALL COORDINATE ANY AND ALL WORK WITH OTHER TRADES INVOLVED IN THE PROJECT, PRIOR TO INSTALLATION OF ELEC. EQUIPMENT, SO AS TO AVOID CONFLICTS DURING CONSTRUCTION AND TO ALLOW FOR OPTIMUM MAINTENANCE AND WORKING SPACE.

5. ALL BRANCH CIRCUITS SHALL BE IN ZINC-COATED EMT OR RIGID CONDUIT AS PERMITTED OR REQUIRED BY THE NATIONAL ELECTRICAL CODE. SCHEDULE 40 PVC CONDUIT MAY BE USED ONLY FOR THE SECONDARY UNDERGROUND SERVICE, THE UNDERGROUND TELEPHONE SERVICE CONDUIT, AND BRANCH CIRCUIT TELEPHONE SYSTEM CONDUITS LOCATED BELOW THE FLOOR SLAB ON GRADE OR BURIED ON THE EXTERIOR OF THE BUILDING, OR IN CONCRETE BLOCK WALLS. ALL CONDUIT SHALL BE 3/4" MINIMUM SIZE EMT FITTINGS SHALL BE STEEL COMPRESSION OR SET SCREW TYPE.

6. ALL CONDUCTORS SHALL BE COPPER TYPE THHN OR THWN, SOLID FOR #10 AWG OR #12 AWG, AND STRANDED FOR ALL LARGER SIZES. MINIMUM CONDUCTOR SIZE SHALL BE #12.

7. ALL WIRE AND CONDUIT SIZES ARE BASED ON 75° C THHN WIRE UNLESS OTHERWISE NOTED. ALL TERMINATIONS & DEVICES SHALL BE RATED FOR 75°C.

8. CONDUITS MAY BE RUN EXPOSED IN MECHANICAL AREAS. CONDUITS SHALL BE RUN PARALLEL OR PERPENDICULAR TO STRUCTURAL ELEMENTS AND SHALL BE RUN IN GROUPS. SEAL ALL PENETRATIONS AIR TIGHT AROUND ALL CONDUITS WHEN PASSING INTO MECHANICAL ROOMS.

9. ALL LIGHT FIXTURES SHALL BE SUPPORTED INDEPENDENTLY OF THE SUSPENDED CEILING SYSTEM.

10. WHERE FIRST OUTLET ON BRANCH CIRCUIT IS GREATER THAN 65 FEET FROM THE PANELBOARD, SEE VOLTAGE DROP SCHEDULE.

11. ALL MOUNTING HEIGHTS ARE GIVEN TO THE BOTTOM OF THE DEVICE UNLESS NOTED OTHERWISE.

12. THE LOCATION OF ALL WALL MOUNTED DEVICES, INCLUDING MOUNTING HEIGHTS, SHALL BE FIELD VERIFIED PRIOR TO INSTALLATION.

13. ALL FUSES, DISCONNECT SWITCHES, AND BREAKER SIZES, SHOWN FOR MECHANICAL EQUIPMENT, SHALL BE VERIFIED BEFORE THE PURCHASE OR INSTALLATION OF SAID EQUIPMENT, WITH THE EQUIPMENT SUPPLIER AND THE CONTRACTOR.

14. ALL DISCONNECT SWITCHES ARE TO BE FUSIBLE TYPE. FUSE IN ACCORDANCE WITH NAMEPLATE DATA WITH DUAL ELEMENT TYPE FUSES.

15. THE CONTRACTOR SHALL PROVIDE ALL NECESSARY DISCONNECTS, SWITCHES, AND RECEPTACLES UNDER THE BID AND SHALL INCLUDE ALL NECESSARY CIRCUITS TO AND FINAL CONNECTIONS TO THE EQUIPMENT PROVIDED BY ALL SUPPLIERS, UNLESS NOTED OTHERWISE BY OTHER DISCIPLINES. COORDINATE CLOSELY.

16. ALL ELECTRICAL EQUIPMENT SHALL BE INSTALLED SO THAT ALL CODE-REQUIRED AND MANUFACTURER-RECOMMENDED SERVICING CLEARANCES ARE MAINTAINED. INSTALLATIONS SHALL FULLY COMPLY WITH NEC 110.26 AND NEC 408.18 FOR CLEARANCE REQUIREMENTS.

17. COORDINATE LOCATIONS OF ALL LIGHT FIXTURES WITH THE REFLECTED CEILING PLANS. LIGHT FIXTURES INSTALLED IN MECHANICAL AREAS SHALL AVOID MECHANICAL PIPING, EQUIPMENT, DUCTWORK, ETC.

18. PROVIDE GROUNDING CONDUCTOR FOR ALL CIRCUITS PER N.E.C. AND BUILDING GROUND SHALL MEET ALL REQUIREMENTS OF NEC 250.

19. GROUND TELEPHONE EQUIPMENT PER J-607 STD AND TIA REQUIREMENTS.

20. THE CONTRACTOR SHALL PATCH ANY WALL, CEILING, OR FLOOR OPENINGS AND PENETRATIONS RESULTING FROM DEMOLITION OR NEW WORK IN EXISTING AREAS.

21. ALL MULTIWIRE BRANCH CIRCUITS SHALL HAVE MULTIPOLE BREAKERS AS REQUIRED BY NEC 210.4(B).

22. ALL CIRCUITS SHALL BE TESTED WITH 500 VOLT TESTER PRIOR TO ENERGIZING.

23. PROVIDE PULL WIRE IN ALL EMPTY CONDUIT FOR FUTURE SYSTEMS.

24. CONDUIT SHALL BE LABELED EVERY TEN FEET.

25. THE CONTRACTOR IS RESPONSIBLE FOR PROPERLY DISPOSING OF ALL WASTE MATERIALS, DEMO MATERIALS AND OTHER TRASH. THIS INCLUDES BUT IS NOT LIMITED TO PROPER DISPOSAL OF MERCURY CONTAINING LAMPS, RECYCLABLE MATERIALS ETC.

26. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO COORDINATE W/ ALL OTHER TRADES REGARDING VOLTAGES, LOADS, CIRCUIT BREAKERS, ETC. PRIOR TO BEGINNING ANY WORK.

27. AS USED ON THESE DOCUMENTS, THE WORD "PROVIDE" SHALL MEAN TO FURNISH AND INSTALL THE ITEM OR EQUIPMENT AND MAKE THE FINAL CONNECTION AS REQUIRED.

28. CONTRACTOR IS RESPONSIBLE TO COMPLY WITH ALL REQUIREMENTS OF THE 2012 INTERNATIONAL BUILDING CODE, ACCESSIBILITY CODE WHICH ARE APPLICABLE TO THIS PROJECT REGARDLESS OF WHETHER ALL DETAILS ARE INDICATED ON PLANS.

29. IT IS NOTED THAT IF TELEPHONE SERVICE IS NOT LOCATED WITHIN 20' OF ELECTRICAL SERVICE, THEN PROVIDE SEPARATE GROUNDING ELECTRODE AS REQUIRED PER NEC 800.

30. CONTRACTOR SHALL VERIFY ALL AREAS THAT ARE USED AS A RETURN PLENUM AND PROVIDE PLENUM RATED CABLE FOR ALL CABLES. ALL CABLES IN A PLENUM SHALL BE RUN IN METAL CONDUIT. THIS INCLUDES ALL TELECOMMUNICATIONS, FIRE ALARM, OR CONTROL WIRING ABOVE CEILING.

31. PROVIDE 3"W x 5"L HARD PLASTIC PLACARD WITH BLACK LETTERING ENGRAVED ON A WHITE BACKGROUND FOR PANEL, ALL DISCONNECT SWITCHES, AND EQUIPMENT CONTROLLER. PLACARD SHALL BE ATTACHED WITH RIVETS TO THE COVER IN PLAIN VIEW AS TO NOT CAUSE INTERNAL DAMAGE (i.e. PANEL NAME, VOLT, AMPERE, PHASE, AND SOURCE POWER FED FROM, ETC.)

32. ALL NEW RECEPTACLES, SWITCHES, AND LIGHTING CIRCUITS SHALL HAVE A PERMANENT, MACHINE PRINTED LABEL FOR POWER SOURCE AND BRANCH CIRCUIT NUMBER ON THE DEVICE/BOX COVER.

ELECTRICAL LEGEND

PLANS

SYMBOLS SHOWN BELOW ARE TO INDICATE NEW DEVICES OR NEW LOCATIONS OF EXISTING DEVICES. SEE LINETYPE LEGEND FOR DISTINCTION OF EXISTING DEVICES TO REMAIN AND DEMOLITION DEVICES.

HOME RUN TO PANEL

BRANCH CIRCUIT

SINGLE POLE WALL SWITCH

3-WAY WALL SWITCH

4-WAY WALL SWITCH

SEE MOTION SENSOR LEGEND FOR THIS AND OTHER SWITCH TYPES.

MINIMUM SIZE PER CKT BKR

44" A.F.F. OR AS NOTED

ALL DUPLEX AND QUAD RECEPTACLES SHALL BE NEMA 5-20R UNLESS NOTED OTHERWISE.

DUPLEX RECEPTACLE

ISOLATED GROUND DUPLEX

POWER RECEPTACLE

QUAD RECEPTACLE

TELECOMMUNICATIONS WALL OUTLET – 18" A.F.F. OR AS NOTED (RUN 1-1 1/4" EMT HOMERUN TO TELECOMMUNICATIONS ROOM ON THIS FLOOR.) PROVIDE 2-CAT6, PLENUM-RATED CABLES AND CONDUIT BUSHINGS.

SIPRNET OUTLET

TELEVISION WALL OUTLET – 16" A.F.F. RUN RG6 IN 3/4" EMT TO TELEPHONE BACKBOARD OR AS INDICATED ON PLANS.

JUNCTION BOX

TELEPHONE BACKBOARD – 4'x8'x3/4" FIRE-TREATED PLYWOOD. PAINT GRAY – PULL #6 GROUND WIRE AND TERMINATE WITH 1/4"x4"x12" GROUND BAR WITH HOLES EVERY 1". MOUNT TO BACKBOARD WITH STAND-OFF INSULATORS.

DISCONNECT SWITCH – FUSIBLE

MOTOR SWITCH

SLIDE TYPE DIMMER SWITCH APPROPRIATE FOR LOAD SERVED – 44" AFF

ELECTRICAL TRANSFORMER

ELECTRICAL PANEL

OVERHEAD FIXTURE OR AS NOTED. SEE FIXTURE SCHEDULE

DOWNLIGHT / PENDANT STYLE. SEE FIXTURE SCHEDULE.

WALL MOUNT. SEE FIXTURE SCHEDULE.

FLOOD / TRACK HEAD STYLE. SEE FIXTURE SCHEDULE.

POLE FIXTURE. SEE FIXTURE SCHEDULE.

EXIT SIGN, FACES AND ARROWS AS INDICATED. SEE FIXTURE SCHEDULE.

EMERGENCY FIXTURE. SEE FIXTURE SCHEDULE.

COMBO EMERGENCY / EXIT FIXTURE. SEE FIXTURE SCHEDULE.

SLASHES OR HALF SHADING INDICATE FIXTURES CONNECTED AHEAD OF ALL SWITCHING TO OPERATE AS NIGHT LIGHTS (FIXTURES WILL BE ON 24/7)

DETAILS

A

ELECTRICAL PANEL OR AS NOTED

C.T.

C.T. CABINET

M

METER BASE AND METER

200/3

200A

FRAME SIZE

FUSE SIZE

FUSIBLE DISCONNECT, FRAME AND FUSE SIZE AS INDICATED.

T

112.5

DESIGNATION

KVA RATING

TRANSFORMER, SIZE AND DESIGNATION AS NOTED. PRIMARY VOLTAGE AS NOTED FOR PRIMARY FEED. SECONDARY VOLTAGE AS NOTED FOR LOAD SUPPLIED.

20X4

CONTACTOR, AMPACITY / POLES AS INDICATED

T.C.

TIMECLOCK

SPD

SURGE PROTECTIVE DEVICE

SERVICE GROUND

LINETYPES

NEW DEVICE OR RELOCATED EXISTING DEVICE.

EXISTING DEVICE TO REMAIN.

EXISTING DEVICE TO BE REMOVED OR RELOCATED.

NEW UNDERGROUND OR UNDERSLAB CONNECTION. EXISTING AND DEMO UNDERGROUND IS NOTED WITH EXISTING OR DEMO LINETYPE. NEW CONNECTIONS NOT SPECIFICALLY SHOWN WITH UNDERGROUND LINETYPE ARE NOT NECESSARILY REQUIRED TO BE RUN OVERHEAD UNLESS NOTED AS SUCH.

SEE WALL RATING LEGEND FOR WALL TYPES AND SYMBOLS.

EXAMPLES OF EXISTING AND DEMO SYMBOLS USING LINETYPES ABOVE

EXISTING DUPLEX RECEPTACLE TO REMAIN.

EXISTING QUAD RECEPTACLE TO REMAIN.

EXISTING TELECOMMUNICATIONS OUTLET TO REMAIN.

EXISTING PANEL TO REMAIN.

EXISTING FLUORESCENT FIXTURE TO REMAIN.

EXISTING SWITCH TO REMAIN.

EXISTING DUPLEX RECEPTACLE TO BE REMOVED.

EXISTING DATA OUTLET TO BE REMOVED.

EXISTING PANEL TO BE REMOVED.

EXISTING FLUORESCENT FIXTURE TO BE MOVED.

EXISTING FLUORESCENT FIXTURE TO BE REMOVED.

EXISTING SWITCH TO BE REMOVED.

VOLTAGE DROP SCHEDULE

120 VOLT BRANCH CIRCUITS UP TO 8 AMPS (<1.0 KVA)

RUN DISTANCE IN FEET

WIRE SIZE AWG

1' – 120'

121' – 190'

191' – 300'

301' – 470'

#12

#10

#8

#6

120 VOLT BRANCH CIRCUITS 9 AMPS TO 14 AMPS (1-1.7 KVA)

RUN DISTANCE IN FEET

WIRE SIZE AWG

1' – 65'

66' – 110'

111' – 170'

171' – 270'

#12

#10

#8

#6

277 VOLT BRANCH CIRCUITS UP TO 14 AMPS (<3.9 KVA)

RUN DISTANCE IN FEET

WIRE SIZE AWG

1' – 160'

161' – 250'

251' – 390'

391' – 620'

#12

#10

#8

#6

WIRE SIZES INDICATED IN GENERAL NOTES AND CONNECTIONS SCHEDULES ARE MINIMUM WIRE SIZES. CONTRACTOR SHALL UPSIZE WIRES BASED ON LOAD AND LENGTH OF RUN AS INDICATED IN SCHEDULE ABOVE.

ELECTRICAL ABBREVIATIONS

A

INDICATES A DEVICE IS TO BE MOUNTED WITH BOTTOM OF BOX 1 1/2" ABOVE BACKSPLASH UNLESS NOTED OTHERWISE.

AFF

ABOVE FINISHED FLOOR

AG

COMBINATION OF 'A' AND 'G'

ARCH

ARCHITECT

C

INDICATES A DEVICE IS TO BE FLUSH MOUNTED IN CEILING TILE.

EX.

EXISTING

EXT.

EXTERIOR

FAH

FAHRENHEIT

FURN

FURNITURE

G

INDICATES A DEVICE WITH INTEGRAL GROUND FAULT INTERRUPTER (GFI) PROTECTION.

GFI

SAME AS 'G'

IG

DEVICE SHALL HAVE ISOLATED GROUND AND WILL REQUIRE ISOLATED GROUND CIRCUITRY.

J.B.

JUNCTION BOX

NTS

NOT TO SCALE

OC

ON CENTER

PROV

PROVIDED BY

S

INDICATES DEVICE IS TO BE SURFACE MOUNTED.

W/

WITH

WP

INDICATES A DEVICE THAT IS WEATHER-PROOF AND RATED FOR EXTERIOR TEMPERATURES.


DESIGNED & ENGINEERED BY:




CRENSHAW CONSULTING


6066

11000E 12000E 13000E 14000E 15000E 16000E 17000E 18000E 19000E 20000E 21000E 22000E 23000E 24000E 25000E 26000E 27000E 28000E 29000E 30000E 31000E 32000E 33000E 34000E 35000E 36000E 37000E 38000E 39000E 40000E 41000E 42000E 43000E 44000E 45000E 46000E 47000E 48000E 49000E 50000E 51000E 52000E 53000E 54000E 55000E 56000E 57000E 58000E 59000E 60000E 61000E 62000E 63000E 64000E 65000E 66000E 67000E 68000E 69000E 70000E 71000E 72000E 73000E 74000E 75000E 76000E 77000E 78000E 79000E 80000E 81000E 82000E 83000E 84000E 85000E 86000E 87000E 88000E 89000E 90000E 91000E 92000E 93000E 94000E 95000E 96000E 97000E 98000E 99000E 100000E 101000E 102000E 103000E 104000E 105000E 106000E 107000E 108000E 109000E 110000E 111000E 112000E 113000E 114000E 115000E 116000E 117000E 118000E 119000E 120000E 121000E 122000E 123000E 124000E 125000E 126000E 127000E 128000E 129000E 130000E 131000E 132000E 133000E 134000E 135000E 136000E 137000E 138000E 139000E 140000E 141000E 142000E 143000E 144000E 145000E 146000E 147000E 148000E 149000E 150000E 151000E 152000E 153000E 154000E 155000E 156000E 157000E 158000E 159000E 160000E 161000E 162000E 163000E 164000E 165000E 166000E 167000E 168000E 169000E 170000E 171000E 172000E 173000E 174000E 175000E 176000E 177000E 178000E 179000E 180000E 181000E 182000E 183000E 184000E 185000E 186000E 187000E 188000E 189000E 190000E 191000E 192000E 193000E 194000E 195000E 196000E 197000E 198000E 199000E 200000E 201000E 202000E 203000E 204000E 205000E 206000E 207000E 208000E 209000E 210000E 211000E 212000E 213000E 214000E 215000E 216000E 217000E 218000E 219000E 220000E 221000E 222000E 223000E 224000E 225000E 226000E 227000E 228000E 229000E 230000E 231000E 232000E 233000E 234000E 235000E 236000E 237000E 238000E 239000E 240000E 241000E 242000E 243000E 244000E 245000E 246000E 247000E 248000E 249000E 250000E 251000E 252000E 253000E 254000E 255000E 256000E 257000E 258000E 259000E 260000E 261000E 262000E 263000E 264000E 265000E 266000E 267000E 268000E 269000E 270000E 271000E 272000E 273000E 274000E 275000E 276000E 277000E 278000E 279000E 280000E 281000E 282000E 283000E 284000E 285000E 286000E 287000E 288000E 289000E 290000E 291000E 292000E 293000E 294000E 295000E 296000E 297000E 298000E 299000E 300000E 301000E 302000E 303000E 304000E 305000E 306000E 307000E 308000E 309000E 310000E 311000E 312000E 313000E 314000E 315000E 316000E 317000E 318000E 319000E 320000E 321000E 322000E 323000E 324000E 325000E 326000E 327000E 328000E 329000E 330000E 331000E 332000E 333000E 334000E 335000E 336000E 337000E 338000E 339000E 340000E 341000E 342000E 343000E 344000E 345000E 346000E 347000E 348000E 349000E 350000E 351000E 352000E 353000E 354000E 355000E 356000E 357000E 358000E 359000E 360000E 361000E 362000E 363000E 364000E 365000E 366000E 367000E 368000E 369000E 370000E 371000E 372000E 373000E 374000E 375000E 376000E 377000E 378000E 379000E 380000E 381000E 382000E 383000E 384000E 385000E 386000E 387000E 388000E 389000E 390000E 391000E 392000E 393000E 394000E 395000E 396000E 397000E 398000E 399000E 400000E 401000E 402000E 403000E 404000E 405000E 406000E 407000E 408000E 409000E 410000E 411000E 412000E 413000E 414000E 415000E 416000E 417000E 418000E 419000E 420000E 421000E 422000E 423000E 424000E 425000E 426000E 427000E 428000E 429000E 430000E 431000E 432000E 433000E 434000E 435000E 436000E 437000E 438000E 439000E 440000E 441000E 442000E 443000E 444000E 445000E 446000E 447000E 448000E 449000E 450000E 451000E 452000E 453000E 454000E 455000E 456000E 457000E 458000E 459000E 460000E 461000E 462000E 463000E 464000E 465000E 466000E 467000E 468000E 469000E 470000E 471000E 472000E 473000E 474000E 475000E 476000E 477000E 478000E 479000E 480000E 481000E 482000E 483000E 484000E 485000E 486000E 487000E 488000E 489000E 490000E 491000E 492000E 493000E 494000E 495000E 496000E 497000E 498000E 499000E 500000E 501000E 502000E 503000E 504000E 505000E 506000E 507000E 508000E 509000E 510000E 511000E 512000E 513000E 514000E 515000E 516000E 517000E 518000E 519000E 520000E 521000E 522000E 523000E 524000E 525000E 526000E 527000E 528000E 529000E 530000E 531000E 532000E 533000E 534000E 535000E 536000E 537000E 538000E 539000E 540000E 541000E 542000E 543000E 544000E 545000E 546000E 547000E 548000E 549000E 550000E 551000E 552000E 553000E 554000E 555000E 556000E 557000E 558000E 559000E 560000E 561000E 562000E 563000E 564000E 565000E 566000E 567000E 568000E 569000E 570000E 571000E 572000E 573000E 574000E 575000E 576000E 577000E 578000E 579000E 580000E 581000E 582000E 583000E 584000E 585000E 586000E 587000E 588000E 589000E 590000E 591000E 592000E 593000E 594000E 595000E 596000E 597000E 598000E 599000E 600000E 601000E 602000E 603000E 604000E 605000E 606000E 607000E 608000E 609000E 610000E 611000E 612000E 613000E 614000E 615000E 616000E 617000E 618000E 619000E 620000E 621000E 622000E 623000E 624000E 625000E 626000E 627000E 628000E 629000E 630000E 631000E 632000E 633000E 634000E 635000E 636000E 637000E 638000E 639000E 640000E 641000E 642000E 643000E 644000E 645000E 646000E 647000E 648000E 649000E 650000E 651000E 652000E 653000E 654000E 655000E 656000E 657000E 658000E 659000E 660000E 661000E 662000E 663000E 664000E 665000E 666000E 667000E 668000E 669000E 670000E 671000E 672000E 673000E 674000E 675000E 676000E 677000E 678000E 679000E 680000E 681000E 682000E 683000E 684000E 685000E 686000E 687000E 688000E 689000E 690000E 691000E 692000E 693000E 694000E 695000E 696000E 697000E 698000E 699000E 700000E 701000E 702000E 703000E 704000E 705000E 706000E 707000E 708000E 709000E 710000E 711000E 712000E 713000E 714000E 715000E 716000E 717000E 718000E 719000E 720000E 721000E 722000E 723000E 724000E 725000E 726000E 727000E 728000E 729000E 730000E 731000E 732000E 733000E 734000E 735000E 736000E 737000E 738000E 739000E 740000E 741000E 742000E 743000E 744000E 745000E 746000E 747000E 748000E 749000E 750000E 751000E 752000E 753000E 754000E 755000E 756000E 757000E 758000E 759000E 760000E 761000E 762000E 763000E 764000E 765000E 766000E 767000E 768000E 769000E 770000E 771000E 772000E 773000E 774000E 775000E 776000E 777000E 778000E 779000E 780000E 781000E 782000E 783000E 784000E 785000E 786000E 787000E 788000E 789000E 790000E 791000E 792000E 793000E 794000E 795000E 796000E 797000E 798000E 799000E 800000E 801000E 802000E 803000E 804000E 805000E 806000E 807000E 808000E 809000E 810000E 811000E 812000E 813000E 814000E 815000E 816000E 817000E 818000E 819000E 820000E 821000E 822000E 823000E 824000E 825000E 826000E 827000E 828000E 829000E 830000E 831000E 832000E 833000E 834000E 835000E 836000E 837000E 838000E 839000E 840000E 841000E 842000E 843000E 844000E 845000E 846000E 847000E 848000E 849000E 850000E 851000E 852000E 853000E 854000E 855000E 856000E 857000E 858000E 859000E 860000E 861000E 862000E 863000E 864000E 865000E 866000E 867000E 868000E 869000E 870000E 871000E 872000E 873000E 874000E 875000E 876000E 877000E 878000E 879000E 880000E 881000E 882000E 883000E 884000E 885000E 886000E 887000E 888000E 889000E 890000E 891000E 892000E 893000E 894000E 895000E 896000E 897000E 898000E 899000E 900000E 901000E 902000E 903000E 904000E 905000E 906000E 907000E 908000E 909000E 910000E 911000E 912000E 913000E 914000E 915000E 916000E 917000E 918000E 919000E 920000E 921000E 922000E 923000E 924000E 925000E 926000E 927000E 928000E 929000E 930000E 931000E 932000E 933000E 934000E 935000E 936000E 937000E 938000E 939000E 940000E 941000E 942000E 943000E 944000E 945000E 946000E 947000E 948000E 949000E 950000E 951000E 952000E 953000E 954000E 955000E 956000E 957000E 958000E 959000E 960000E 961000E 962000E 963000E 964000E 965000E 966000E 967000E 968000E 969000E 970000E 971000E 972000E 973000E 974000E 975000E 976000E 977000E 978000E 979000E 980000E 981000E 982000E 983000E 984000E 985000E 986000E 987000E 988000E 989000E 990000E 991000E 992000E 993000E 994000E 995000E 996000E 997000E 998000E 999000E 1000000E 1001000E 1002000E 1003000E 1004000E 1005000E 1006000E 1007000E 1008000E 1009000E 1010000E 1011000E 1012000E 1013000E 1014000E 1015000E 1016000E 1017000E 1018000E 1019000E 1020000E 1021000E 1022000E 1023000E 1024000E 1025000E 1026000E 1027000E 1028000E 1029000E 1030000E 1031000E 1032000E 1033000E 1034000E 1035000E 1036000E 1037000E 1038000E 1039000E 1040000E 1041000E 1042000E 1043000E 1044000E 1045000E 1046000E 1047000E 1048000E 1049000E 1050000E 1051000E 1052000E 1053000E 1054000E 1055000E 1056000E 1057000E 1058000E 1059000E 1060000E 1061000E 10







APPROVED	DATE	DESCRIPTION	SYMBOL	DATE	APPROVED
 DESIGNED & ENGINEERED BY:   APPROVED ACTIVITY - SATISFACTORY TO DATE FOR EFD FOR COMMANDER NAVFAC DATE A/E JTR DESIGN JTR DRAWN JTR REVIEW JRC QC JRC CHIEF ARCH/ENGR PROJECT MANAGER FIRE PROTECTION BRANCH MANAGER DESIGN DIRECTOR					
NAVAL FACILITIES ENGINEERING COMMAND MARINE CORPS AIR STATION, CHERRY POINT, N.C. CONSTRUCT COMPOSITE SHOP ADDITION, BUILDING 4224 PARTIAL FLOOR PLAN / ELECTRICAL DEMOLITION					
STA. PROJ. NO. 6328570 SPEC. NO. CONSTR. CONTR. NO. NAVFAC DRAWING NO. 12685653 SHEET 40 OF 45 E-101					
100% Final Submittal					








**PARTIAL FLOOR PLAN – LIGHTING**  
SCALE: 1/8"=1'-0"


- PLAN NOTES:**
- 1. CONNECT EMERGENCY AND EXIT LIGHTS AHEAD OF LOCAL SWITCH AS REQUIRED. (TOTAL FIXTURE UNSWITCHED)
  - 2. FOR THIS FIXTURE, REMOTE BATTERY SHALL BE INSIDE BUILDING AND EXTERIOR EMERGENCY LAMPS ARE INTEGRAL TO EXTERIOR LIGHT MOUNTED ON BUILDING. EMERGENCY LAMPS SHALL ONLY COME ON IN THE EVENT OF POWER LOSS. CONTRACTOR SHALL CONNECT BATTERY AHEAD OF EXTERIOR LIGHTING CONTACTOR (TOTAL FIXTURE UNSWITCHED).
  - 3. CONNECT NEW FIXTURE AT SAME LOCATION AS REMOVED FIXTURE, AND TO EXISTING LIGHTING CIRCUIT CURRENTLY SERVING THAT FIXTURE.

**LIGHTING NOTES:**


- 1. LINEAR HIGH BAY FIXTURES, TYPE 'A', SHALL BE MOUNTED SUCH THAT THE BOTTOM OF THE FIXTURE IS AT 17 FEET A.F.F.
- 2. EMERGENCY WALLPACK FIXTURES, TYPE 'EM', SHALL BE MOUNTED AT 12 FEET A.F.F.
- 3. EXTERIOR WALLPACK FIXTURES, TYPE 'BE', SHALL BE MOUNTED AT 12 FEET A.F.F.
- 4. LINEAR HIGH BAY FIXTURES, TYPE 'A', SHALL BE PROVIDED WITH WIRE GUARDS.



APPROVED	DATE	DESCRIPTION	DATE	APPROVED
DESIGNED & ENGINEERED BY:				
APPROVED				
ACTIVITY – SATISFACTORY TO				
DATE				
APPROVED				
FOR EFD FOR COMMANDER NAVFAC				
DATE				
A/E				
JTR DESIGN				
JTR DRAWN				
JTR REVIEW				
JRC QC				
JRC CHIEF ARCH/ ENGR				
PROJECT MANAGER				
FIRE PROTECTION				
BRANCH MANAGER				
DESIGN DIRECTOR				
NAVAL FACILITIES ENGINEERING COMMAND				
MARINE CORPS AIR STATION, CHERRY POINT, N.C.				
CONSTRUCT COMPOSITE SHOP				
ADDITION, BUILDING 4224				
PARTIAL FLOOR PLAN (1) OF 1 (1) OF 1				
STA. PROJ. NO. 6328570				
SPEC. NO.				
CONSTR. CONTR. NO.				
NAVFAC DRAWING NO. 12685655				
SHEET 42 OF 45				
E-100				
100% Final Submittal				







System No. W-L-1001

June 15, 2005

F Ratings — 1, 2, 3 and 4 Hr (See Items 2 and 3)  
T Ratings — 0, 1, 2, 3, and 4 Hr (See Item 3)  
L Rating At Ambient — less than 1 CFM/sq ft  
L Rating At 400 F — less than 1 CFM/sq ft

1. Wall Assembly —The 1, 2, 3 or 4 hr fire-rated gypsum wallboard/stud wall assembly shall be constructed of the materials and in the manner described in the individual U300 or U400 Series Wall or Partition Designs in the UL Fire Resistance Directory and shall include the following construction features:

A. Studs —Wall framing may consist of either wood studs (max 2 h fire rated assemblies) or steel channel studs. Wood studs to consist of nom 2 by 4 in. (51 by 102 mm) lumber spaced 16 in. (406 mm) OC with nom 2 by 4 in. (51 by 102 mm) lumber end plates and cross braces. Steel studs to be min 3-5/8 in. (92 mm) wide by 1-3/8 in. (35 mm) deep channels spaced max 24 in. (610 mm) OC.

B. Gypsum Board\* —Nom 1/2 or 5/8 in. (13 or 16 mm) thick, 4 ft. (122 cm) wide with square or tapered edges. The gypsum wallboard type, thickness, number of layers, fastener type and sheet orientation shall be as specified in the individual U300 or U400 Series Design in the UL Fire Resistance Directory. Max diam of opening is 26 in. (660 mm).

2. Through-Penetrant —One metallic pipe, conduit or tubing installed either concentrically or eccentrically within the firestop system. The annular space between pipe, conduit or tubing and periphery of opening shall be min of 0 in. / (0 mm). (point contact) to max 2 in. (51 mm) Pipe, conduit or tubing to be rigidly supported on both sides of wall assembly. The following types and sizes of metallic pipes, conduits or tubing may be used:

A. Steel Pipe —Nom 24 in. (610 mm) diam (or smaller) Schedule 10 (or heavier) steel pipe.

B. Iron Pipe —Nom 24 in. (610 mm) diam (or smaller) service weight (or heavier) cast iron soil pipe, nom 12 in (305 mm) diam (or smaller) or Class 50 (or heavier) ductile iron pressure pipe.

C. Conduit —Nom 6 in. (152 mm) diam (or smaller) steel conduit or nom 4 in (102 mm) diam (or smaller) steel electrical metallic tubing

D. Copper Tubing —Nom 6 in. (152 mm) diam (or smaller) Type L (or heavier) copper tubing

E. Copper Pipe —Nom 6 in. (152 mm) diam (or smaller) Regular (or heavier) copper pipe.

F. Through Penetrating Product\* —Flexible Metal Piping The following types of steel flexible metal gas piping may be used:

1. Nom 2 in. (51 mm) diam (or smaller) steel flexible metal gas piping. Plastic covering on piping may or may not be removed on both sides of floor or wall assembly.

OMEGA FLEX INC

2. Nom 1 in. (25 mm) diam (or smaller) steel flexible metal gas piping. Plastic covering on piping may or may not be removed on both sides of floor or wall assembly.

GASTITE, DIV OF TITEXLEX

3. Nom 1 in. (25 mm) diam (or smaller) steel flexible metal gas piping. Plastic covering on piping may or may not be removed on both sides of floor or wall assembly.

WARD MFG L L C

3. Fill, Void or Cavity Material\* —Caulk or Sealant —Min 5/8, 1-1/4, 1-7/8 and 2-1/2 in. (16, 32, 48 and 64 mm) thickness of caulk for 1, 2, 3 and 4 hr rated assemblies, respectively, applied within annulus, flush with both surfaces of wall. Min 1/4 in. (6 mm) diam bead of caulk applied to gypsum board/penetrant interface at point contact location on both sides of wall. The hourly F Rating of the firestop system is dependent upon the hourly fire rating of the wall assembly in which it is installed, as shown in the following table. The hourly T Rating of the firestop system is dependent upon the type or size of the pipe or conduit and the hourly fire rating of the wall assembly in which it is installed, as tabulated below:

Max Pipe or Conduit Diam, in (mm)	F Rating, Hr	T Rating, Hr
1 (25)	1 or 2	0+, 1 or 2
1 (25)	3 or 4	3 or 4
4 (102)	1 or 2	0
6 (152)	3 or 4	0
12 (305)	1 or 2	0

+When copper pipe is used, T Rating is 0 h.

3M COMPANY —CP 25WB+ or FB-3000 WT.

\*Bearing the UL Classification Mark

FOR FRAMED WALLS ONLY

1,2,3, OR 4 HOUR PENETRATION FIRESTOP

FOR METALLIC PIPE, CONDUIT, OR TUBING

SCALE: NONE

Panel: SPB-9		800 AMP		Poles: 42 Voltage: 277/480	
LOAD SERVED		MAIN LUGS ONLY		Phase: 3 Wires: 4	
	KVA	BRKR.	Ø	BRKR.	KVA
SPARE			1 A 2		
		50/3	3 B 4	50/3	
			5 C 6		
			7 A 8	5.3	
SPARE		50/3	9 B 10	30/3	5.3
			11 C 12	5.3	
	24.1		13 A 14		
AHU-1	24.1	90/3	15 B 16	70/3	
			17 C 18		
			19 A 20	20/1 1.9	DISASSEMBLY SHOP LIGHTING
SPARE		100/3	21 B 22	SPACE	SPACE
			23 C 24	SPACE	SPACE
			25 A 26		
SPARE		70/3	27 B 28	110/3	SPACE
			29 C 30		
			31 A 32	31.0	
CRANE	1.3		33 B 34	175/3	31.0
	1.3	15/3	35 C 36		EXISTING
SPACE			37 A 38	35.4	
SPACE			39 B 40	200/3	EXISTING
SPACE			41 C 42	35.4	

Demand Load Summary:		Phase A:		Phase B:		Phase C:		Total Panel Load:	
Lighting:	1.9 KVA	@ 125%	2.4 KVA		99.4 KVA		359.0 Amps		
Largest Motor:	0.0 KVA	@ 125%	0.0 KVA		97.1 KVA		350.4 Amps		
Gen Receptacles:	0.0 KVA	@ 100%	0.0 KVA		97.1 KVA		350.4 Amps		
All Other:	291.2 KVA	@ 100%	291.2 KVA		293.6 KVA		353.1 Amps		

<input checked="" type="checkbox"/> GROUND BAR	<input type="checkbox"/> NEMA 3R	I. MATCH EXISTING AIC.	
<input checked="" type="checkbox"/> SEPARATE NEUTRAL BAR	<input checked="" type="checkbox"/> FEED THRU LUGS		
<input checked="" type="checkbox"/> U.L. S.E. RATED	<input checked="" type="checkbox"/> EXISTING PANEL		
<input checked="" type="checkbox"/> SURFACE MOUNTED	<input type="checkbox"/> EXISTING PANEL		

Panel: SPB-9A		800 AMP		Poles: 42 Voltage: 277/480	
LOAD SERVED		MAIN LUGS ONLY		Phase: 3 Wires: 4	
	KVA	BRKR.	Ø	BRKR.	KVA
SPARE			1 A 2		
		20/3	3 B 4	20/3	
			5 C 6		
			7 A 8	3.5	
SPARE		20/3	9 B 10	20/3	3.5
			11 C 12	3.5	
	5.3		13 A 14	SPACE	SPACE
EX. OVEN	5.3	30/3	15 B 16	SPACE	SPACE
	5.3		17 C 18	SPACE	SPACE
		SPACE	19 A 20		
SPACE		SPACE	21 B 22	40/3	SPACE
SPACE		SPACE	23 C 24		
			25 A 26		
SPACE			27 B 28	40/3	SPACE
			29 C 30		
			31 A 32		
SPACE			33 B 34	40/3	SPACE
			35 C 36		
			37 A 38	SPACE	SPACE
SPACE			39 B 40	SPACE	SPACE
			41 C 42	SPACE	SPACE
	22.1		43 A 44	SPACE	SPACE
EX. TRANSFORMER	22.1	100/3	45 B 46	SPACE	SPACE
	22.1		47 C 48	SPACE	SPACE

Demand Load Summary:		Phase A:		Phase B:		Phase C:		Total Panel Load:	
Lighting:	0.0 KVA	@ 125%	0.0 KVA		30.9 KVA		111.6 Amps		
Largest Motor:	0.0 KVA	@ 125%	0.0 KVA		30.9 KVA		111.6 Amps		
Gen Receptacles:	0.0 KVA	@ 100%	0.0 KVA		30.9 KVA		111.6 Amps		
All Other:	92.2 KVA	@ 100%	92.2 KVA		92.7 KVA		111.5 Amps		

<input checked="" type="checkbox"/> GROUND BAR	<input type="checkbox"/> NEMA 3R	I. MATCH EXISTING AIC.	
<input checked="" type="checkbox"/> SEPARATE NEUTRAL BAR	<input checked="" type="checkbox"/> FEED THRU LUGS		
<input checked="" type="checkbox"/> U.L. S.E. RATED	<input checked="" type="checkbox"/> EXISTING PANEL		
<input checked="" type="checkbox"/> SURFACE MOUNTED	<input type="checkbox"/> EXISTING PANEL		

Panel: RP9B		225/3		Poles: 42 Voltage: 120/208	
LOAD SERVED		MAIN BREAKER		Phase: 3 Wires: 4	
	KVA	BRKR.	Ø	BRKR.	KVA
EX. PRESS	1.5		1 A 2	20/1	
	1.5	20/3	3 B 4	20/1 1.5	EX. WORKBENCH
			5 C 6	20/1 1.5	EX. WORKBENCH
EX. ROTATION STAND	1.5	20/1	7 A 8	20/1 1.5	EX. WORKBENCH
EX. QA RECEPT.	1.0	20/1	9 B 10	20/2	SPACE
EX. WORKBENCH	1.5	20/1	11 C 12		SPACE
EX. COMPUTER RECEPTS.	1.0	20/1	13 A 14	20/1 1.5	EX. ROTATING STAND
EX. LTS & PRINTER RECEPT.	1.2	20/1	15 B 16	SPACE	SPACE
EX. COMPUTER RECEPT.	1.0	20/1	17 C 18	20/1	SPACE
			19 A 20	20/1	SPACE
SPACE			21 B 22	SPACE	SPACE
		60/3	23 C 24	20/2 1.5	EX. FREEZER
SPACE		20/2	25 A 26	1.5	
			27 B 28	20/1 1.5	EX. WORKBENCH
SPACE		SPACE	29 C 30	20/1 1.5	EX. WORKBENCH
SPACE		SPACE	31 A 32	20/1 1.0	EX. QA RECEPTS.
SPACE		SPACE	33 B 34	SPACE	SPACE
SPACE		SPACE	35 C 36		SPACE
SPACE		SPACE	37 A 38	6.0	
SPACE		SPACE	39 B 40	100/3 7.4	NEW PANEL 'N'
SPACE		SPACE	41 C 42		

Demand Load Summary:		Phase A:		Phase B:		Phase C:		Total Panel Load:	
Lighting:	0.0 KVA	@ 125%	0.0 KVA		15.5 KVA		129.2 Amps		
Largest Motor:	0.0 KVA	@ 125%	0.0 KVA		14.1 KVA		117.5 Amps		
Gen Receptacles:	0.0 KVA	@ 100%	0.0 KVA		13.9 KVA		115.8 Amps		
All Other:	43.5 KVA	@ 100%	43.5 KVA		43.5 KVA		120.7 Amps		

<input checked="" type="checkbox"/> GROUND BAR	<input type="checkbox"/> NEMA 3R	I. MATCH EXISTING AIC.	
<input checked="" type="checkbox"/> SEPARATE NEUTRAL BAR	<input checked="" type="checkbox"/> FEED THRU LUGS		
<input checked="" type="checkbox"/> U.L. S.E. RATED	<input checked="" type="checkbox"/> EXISTING PANEL		
<input checked="" type="checkbox"/> SURFACE MOUNTED	<input type="checkbox"/> EXISTING PANEL		

Panel: N		100/3		Poles: 30 Voltage: 120/208	
LOAD SERVED		MAIN BREAKER		Phase: 3 Wires: 4	
	KVA	BRKR.	Ø	BRKR.	KVA
DED. QUAD RECEPT.	1.0	20/1	1 A 2	20/1 0.1	EXTERIOR WALLPACK LIGHTS
DED. QUAD RECEPT.	1.0	20/1	3 B 4	20/1 1.1	MOTORIZED DOOR
DED. QUAD RECEPT.	1.0	20/1	5 C 6	20/1 1.1	MOTORIZED DOOR
DED. QUAD RECEPT.	1.0	20/1	7 A 8	20/1 0.6	RECEPTACLES
DED. QUAD RECEPT.	1.0	20/1	9 B 10	20/1 1.0	DED. QUAD RECEPT.
DED. QUAD RECEPT.	1.0	20/1	11 C 12	20/1	SPACE
DED. QUAD RECEPT.	1.0	20/1	13 A 14	20/1	SPACE
DED. QUAD RECEPT.	1.0	20/1	15 B 16	20/1	SPACE
DED. QUAD RECEPT.	1.0	20/1	17 C 18	20/1	SPACE
DED. QUAD RECEPT.	1.0	20/1	19 A 20	20/1	SPACE
DED. QUAD RECEPT.	1.0	20/1	21 B 22	20/1	SPACE
SPACE		20/1	23 C 24	SPACE	SPACE
SPACE		SPACE	25 A 26	SPACE	SPACE
SPACE		SPACE	27 B 28	SPACE	SPACE
SPACE		SPACE	29 C 30	SPACE	SPACE

Demand Load Summary:		Phase A:		Phase B:		Phase C:		Total Panel Load:	
Lighting:	0.1 KVA	@ 125%	0.1 KVA		4.7 KVA		39.4 Amps		
Largest Motor:	0.0 KVA	@ 125%	0.0 KVA		6.1 KVA		50.8 Amps		
Gen Receptacles:	0.0 KVA	NOTE 2	0.0 KVA		4.1 KVA		34.2 Amps		
All Other:	34.8 KVA	@ 100%	34.8 KVA		34.8 KVA		41.4 Amps		

<input checked="" type="checkbox"/> GROUND BAR	<input type="checkbox"/> NEMA 3R	I. ALL BREAKERS SHALL BE RATED AT 10,000 AIC.	
<input checked="" type="checkbox"/> SEPARATE NEUTRAL BAR	<input checked="" type="checkbox"/> FEED THRU LUGS		
<input checked="" type="checkbox"/> U.L. S.E. RATED	<input checked="" type="checkbox"/> EXISTING PANEL		
<input checked="" type="checkbox"/> SURFACE MOUNTED	<input type="checkbox"/> EXISTING PANEL		

PANEL SCHEDULE NOTES:

\* SEE EQUIPMENT CONNECTION SCHEDULE FOR CIRCUIT BREAKER SIZES.

\*\*\* FOR RECEPTACLE LOADS SHOWN OVER 10.0 KVA, A 100% DIVERSITY FACTOR WAS USED FOR THE FIRST 10.0 KVA, AND A 50% DIVERSITY FACTOR WAS USED FOR THE LOAD OVER 10.0 KVA

1. VALUES FOR DEMAND LOADS INCLUDE ALL CODE FACTORS SUCH AS 125% FOR CONTINUOUS LOADS, 125% LARGEST MOTOR, ETC.

2. CIRCUIT BREAKERS USED FOR HVAC EQUIPMENT SHALL BE "HACR" TYPE.

3. ALL PANEL DIRECTORIES SHALL BE COMPLETED IN ACCORDANCE WITH NEC 408.4.

4. CONTRACTOR SHALL PROVIDE MULTIPOLE BREAKERS IN LIEU OF ALL SINGLE POLE BREAKERS SHOWN WHEN MULTIWIRED BRANCH CIRCUITS ARE INSTALLED PER NEC 210.4(B).


5. CONTRACTOR SHALL LABEL ALL BREAKERS FEEDING EMERGENCY AND EXIT LIGHTING PER NEC 700.12(F).

6. CONTRACTOR SHALL PROVIDE IDENTIFICATION FOR NEW FEEDERS AND ANY NEW BRANCH CIRCUITS PER NEC 200.6, 210.5, AND 215.12.

7. BREAKERS INDICATED AS (L) SHALL HAVE A BREAKER LOCK PROVIDED. I.E. 20/1(L) SHALL BE A 20 AMP SINGLE POLE BREAKER WITH LOCK.

8. BOLDDED TEXT INDICATES A NEW OR CHANGED CIRCUIT ON AN EXISTING PANEL, BOLDDED BREAKERS ARE NEW OR RELOCATED TO LOCATION SHOWN.

9. ENGINEER HAS SHOWN NEW CIRCUITS IN LOCATIONS DETERMINED TO BE SPARE OR SPACE BASED ON PANEL DIRECTORIES AND OTHER AVAILABLE INFORMATION. CONTRACTOR SHALL VERIFY THAT PLACEMENT SHOWN DOES NOT INTERFERE WITH EXISTING CIRCUITS TO REMAIN. VERIFY AVAILABLE CIRCUITS BASED ON NEW AND DEMO PLANS AND CONTACT ENGINEER WITH ANY CONFLICTS.



RISER KEY NOTES:

- PHOTOCELL ON ROOF FACING NORTH TO TURN LIGHTS ON. ADJUST SENSITIVITY AS REQUIRED FOR PROPER OPERATION.
- 7-DAY PROGRAMMABLE TIME CLOCK TO TURN LIGHTS OFF W/ SEASONABLE DAYLIGHT SCHEDULE ADJUSTMENT AND 4 HOUR BATTERY BACKUP.

PARTIAL EXISTING ELECTRICAL RISER DIAGRAM

Scale: NTS

APPROVED

ACTIVITY — SATISFACTORY TO

DATE

APPROVED

FOR EFD FOR COMMANDER NAVFAC

DATE

A/E

JTR DESIGN

JTR DRAWN

JTR REVIEW

JRC QC

JRC CHIEF ARCH/ ENGR

PROJECT MANAGER

FIRE PROTECTION

BRANCH MANAGER

DESIGN DIRECTOR

NAVAL FACILITIES ENGINEERING COMMAND

MARINE CORPS AIR STATION, CHERRY POINT, N.C.

CONSTRUCT COMPOSITE SHOP ADDITION, BUILDING 4224

ELECTRICAL DETAILS

STA. PROJ. NO. 6328570

SPEC. NO.

CONSTR. CONTR. NO.

NAVFAC DRAWING NO. 12685657

SHEET 44 OF 45

E-20

100% Final Submittal



